



		DC18GSE	DC22GSE	DC25GSE	DC30GSE	DC40GSE	DC50GSE
A - Kesselhöhe	mm	1281	1281	1281	1281	1431	1431
B - Kesseltiefe	mm	830	830	1030	1030	1120	1120
C - Kesselbreite	mm	680	680	680	680	680	680
D - Mitte Rauchrohr	mm	945	945	945	945	1095	1095
E - Rauchrohr Ø	mm	148-152	148-152	148-152	148-152	148-152	148-152
F	mm	87	87	87	87	82	78
G	mm	185	185	185	185	184	184
H	mm	1008	1008	1008	1008	1152	1152
CH	mm	256	256	256	256	256	256
I	mm	256	256	256	256	256	256
J - Stutzen Ø	Zoll	1 ½	1 ½	1 ½	1 ½	2	2
Nennleistung	kW	19	23	25	29,8	40	49
mind. Puffervolumen	Liter	1045	1265	1375	1639	2200	2695
Wirkungsgrad	%	90,3	90,7	90,5	90,8	90,5	92,0
Füllraumtiefe	mm	330	330	530	530	530	530
Füllraumvolumen	dm	85	86	125	125	170	170
Messwert CO	mg/m <sup>3</sup>	152	140	97	73	100	163
Messwert Staub	mg/m <sup>3</sup>	12	14	11	10	9	15
Kesselgewicht	kg	376	373	469	466	548	565
erford. Schornsteinzug	mbar	0,16	0,18	0,18	0,20	0,22	0,24
Abgasmassstrom	kg/s	0,014	0,014	0,017	0,017	0,021	0,025
Abgastemperatur	°C	145	158	132	155	175	183
Alle Kessel der GSE Serie haben ein Saugzugventilator.							